

# MOTO HMEOC 4T 10W30



MOTORCYCLE

Lubricants

## Description

Synthetic lubricant oil for high performance 4-stroke engines with fuel saving properties. High thermal stability and excellent engine care as it is used at high engine revolutions even under high temperatures in hot climates. It particularly cares for the delicate parts such as the gearbox and wet clutches. With Racing HMEOC your engine is always ready to give maximum performance.

## Properties

- Developed according to the demanding HMEOC (High Quality Motorcycle Engine Oil Conception for fuel saving) requirements to contribute towards fuel saving and therefore to protecting the environment by reducing CO2 emissions.
- Results tested on four-stroke motorcycles in extreme working conditions that have shown excellent protection against wear.
- Its formula offers high level performance and, at the same time, ensures adequate friction for couplings coated in oil in the joint engine and transmission lubrication systems in motorcycles (wet clutch).
- Only use when this SAE 10W30 viscosity grade is recommended by the motorcycle manufacturer. It offers fuel savings of up to 8 % and reduced lubricant consumption (\*), thus guaranteeing exceptional lubrication of the engine and transmission.

(\*) Source: Honda Technical Support for Motorcycle Engine Oil Working Group (Low Viscosity Promotion) - 2008 Fuels & Lubricants Steering Committee for Asia

## Quality Levels

- HMEOC (High Quality Motorcycle Engine Oil Conception for Fuel Saving)
- JASO T-903:2011 MA & MA2
- API SJ

## Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			10W30
Density at 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0.859
Viscosity at 100 °C	cSt	ASTM D 445	10.1
Viscosity at 40 °C	cSt	ASTM D 445	63
Viscosity at -25 °C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	147
Flash point, open cup	°C	ASTM D 92	248
Pour point	°C	ASTM D 97	-42
T.B.N.	mg KOH/g	ASTM D 2896	8.2
Sulphated ashes	% in weight	ASTM D 874	1.15
Shear I. Bosch at 100 °C	cSt	ASTM D 3945	9.9
Volatility Noack 250 °C	%	DIN 51581	7.8

A safety information file is available on request.  
[repsol.com](http://repsol.com)

+34 901 111 999

Technical data sheet for Lubricants. Revision 4. October 2014